



Hi-Stat® cling vinyl is a very soft, flexible vinyl which adheres to most clean, high polished smooth surfaces without adhesive.

Hi-Stat

Repositionable – printed decals can be reused if properly handled

Easy removal without leaving a trace of residue behind

No solvents are needed for application or removal

Can be wet applied

For indoor and outdoor use

Made in the U.S.A.

Available in 8 mil white and clear on a 8 pt stayflat paper board liner

Printer Compatibility: HP Indigo, Conventional and UV Offset

Easy to apply and remove from these surfaces:



Applications

Window Advertising

P.O.P. Window Decals

Price Stickers

Automotive Window Decals

LED Screen Protection



STOCKED PRODUCTS ▶

	Finish/Color	SKU #	Size	Thickness	GSM	M Wgt	Sheets/Carton
HP Indigo							
	Gloss White	67120	12" x 18"	8 mil	405	123.3	300
		67121	13" x 19"			140.0	
	Gloss Clear	67125	12" x 18"	8 mil	390	123.3	300
		67126	13" x 19"			140.0	
	Finish/Color		Size	Thickness	GSM	M Wgt	Sheets/Carton
Conventional & UV Offset							
	Gloss White	67225	27" x 20"	8 mil	405	340.0	100
		67226	27" x 38"			640.0	
	Gloss Clear	67230	27" x 20"	8 mil	390	340.0	100
		67231	27" x 38"			640.0	



Nekoosa has 3 conveniently located converting facilities for quick shipping of custom sheets.

TECHNICAL DATA ►

Physical Properties	
Adhesive	None
Film	Flexible Vinyl
Finish	High Gloss
Color	White and Clear
Liner	Paper Board
Film Thickness	8 mil (7.5 ± 0.2 mil)
Liner Thickness	8 pt
Weight	.62#
Adhesion	N/A
Surface Tension	32 Dynes Minimum

Conditions for Use	
Shelf Life	1 year*
Min. Application Temp.	50° F (10° C)
Service Temp. Range	-10° F to 120° F (-23.3° C to 48.9° C)
Outdoor Durability	3 Months**
Indoor Durability	6 months
Water Resistance	Excellent
Chemical Resistance	Excellent***
Material Reuse	Yes†

*When stored at 75° F and 50% relative humidity.
**Mid-continental USA vertical exposure.
***Excellent - commercial window cleaners.
†Printed decals can be reused if properly handled.

Certified for
HP Indigo

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.